

DOME-VF

INTERNAL USE VARIFOCAL DOME CAMERA

FEATURES

- Colour Camera in Metal Dome Housing
- 420 TVL Horizontal Resolution
- Varifocal manual 2.8 to 12mm lens
- Vandal Resistant Design



Signal System	PAL
Effective Pixels	500(H) x 582(V)
Image sensor	1/3" SONY Super HAD CCD
Sensing Area	4.9mm x 3.7mm
Shutter Speed	1/50(1/60) ~ 1/100,000 SEC
Video Output	1.0 Vp-p , 75Ω
Scanning Frequency	Horizontal 15.625KHz Vertical 50Hz
Scanning System	2:1 interlace / internal
Horizontal Resolution	420 TV Lines
Minimum Illumination	0.1 LUX (F1.2)
Gamma Correction	0.45

S/N Ratio	≥ 48dB (AGC OFF)
White Balance	Automatic White Balance
AGC	ON
BLC	ON
Burst Level	1/50
Operating Temp	-10~50°C
Water/Partial Resistance	IP 65
Lens	2.8-12mm Manual Varifocal
Dimensions (cms)	10.5(℄) x 7.5(H)
Weight (Grams)	380
Power Source	DC12V
Power Consumption	120mA (IR OFF)

Elite Security Products

Unit 7, Target Park, Shawbank Rd
Lakeside, Redditch B98 8YN



Telephone: 01527 515150
email: info@espuke.com