

IR-DOME

INTERNAL USE DAY / NIGHT DOME CAMERA

FEATURES

- Integral LED Illumination (10m)
- Colour in Day - Mono in darkness
- Fixed 4mm Lens
- 420TVL Horizontal resolution



IMAGE SENSOR	1/3" Color SONY CCD
EFFECTIVE PIXELS	PAL: 500(H)×582(V) NTSC: 510(H)×492(V)
SIGNAL SYSTEM	PAL/NTSC
RESOLUTION	420TVL
MINIMUM ILLUMINATION	0.2Lux/F2.0, 0Lux(IR On)
LENS	Board Lens 4mm
S/N RATIO	More than 48dB(AGC OFF)
EXPOSURE MODE	EE
ELECTRONIC SHUTTER	PAL:1/50- 1/100,000 sec
SPEED	NTSC: 1/60 - 1/100,000 sec
GAMMA	0.45
WHITE BALANCE	ATM

AGC GAIN CONTROL	Auto
DAY & NIGHT	Auto
SYNC SYSTEM	Internal
INFRARED LUMINARY	24 pcs \varnothing 5 IR-LED
ILLUMINATION DISTANCE	10m
VIDEO OUTPUT	1.0Vp-p,750hms
POWER REQUIREMENT	DC12V
POWER CONSUMPTION	120mA(IR OFF), 350±5%mA(IR ON)
OPERATION TEMP	-10°C --50°C
DIMENSION	95mm(\varnothing)×85mm(H)
WEIGHT (Grams)	170
MATERIAL	Plastic

Elite Security Products

Unit 7, Target Park, Shawbank Rd
Lakeside, Redditch B98 8YN



Telephone: 01527 515150
email: info@espuk.com