

IRDOMEXT-VF

EXTERNAL USE VARIFOCAL DAY / NIGHT DOME CAMERA

FEATURES

- Integral LED Illumination (30m)
- Colour in Day - Mono in darkness
- Varifocal Manual 2.8 to 12mm Lens
- Vandal Resistant Design
- 560TVL Horizontal Resolution
- Wall mount bracket included



Signal System	PAL
Effective Pixels	752(H) x 582(V)
Image sensor	1/3" SONY Super HAD CCD
Sensing Area	4.9mm x 3.7mm
Shutter Speed	1/50(1/60) ~ 1/100,000 SEC
Video Output	1.0Vp-p, 75Ω
Scanning Frequency	Horizontal 15.625KHz Vertical: 50Hz
Scanning System	2:1 interlace / internal
Horizontal Resolution	560 TV Lines
Minimum Illumination	0.01Lu x (F1.2) / 0.00LUX(IN IRMode)
Gamma Correction	0.45
S/N Ratio	≥ 50dB (AGC OFF)

White Balance Automatic	White Balance
AGC	ON
BLC	ON
IR Capability	42 pcs \varnothing 5 IR-LED
IR Illumination Distance	More than 30m
Operating Temp	-10~50°C
Water Resistance	IP 65
Lens	2.8-12mm Manual Varifocal
Dimensions	12(\varnothing) x 8(H)
Weight (Grams)	1185
Power Source	DC12V
Power Consumption	120mA (IR OFF), 450mA (IR ON)

Elite Security Products

Unit 7, Target Park, Shawbank Rd
Lakeside, Redditch B98 8YN



Telephone: 01527 515150
email: info@espuk.com

www.espuk.com