

MINIDOME

INTERNAL DOME CAMERA

FEATURES

- 420 TVL
- Fixed 2.8mm Lens
- 12v DC 120mA



Image Sensor	1/3" SONY SuperHAD CCD
Effective Pixels	PAL: 500(H)×582(V) NTSC: 510(H)×492(V)
Signal System	NTSC/PAL
Horizontal Resolution	420TV Lines
Scanning System	2:1 Interlace
Sync.System	Internal
Minimum Illumination	0.1Lux/F1.2
S/N Ratio	More Than 48dB(AGC OFF)
Gamma	0.45
Electrical Shutter	NTSC: 1/60-1/120,000S PAL: 1/50-1/120,000S

White Balance	ATW
Auto Gain Control	Auto
BLC	Auto
Lens Mount	Built-in Fixed Lens(f=2.8mm)
Video Output	1.0Vp-p(75Ω,Composite)
Power Requirement	DC12V±10% & 200mA
Dimension	94mm(∅)×68mm(H)
Weight Approx	400g
Storage Temperature	-30°C To +60°C
Operating Temperature	-10°C To +45°C

Elite Security Products

Unit 7, Target Park, Shawbank Rd
Lakeside, Redditch B98 8YN



Telephone: 01527 515150
email: info@espuk.com