


TM PRO SHD

TMPROSHD - 4" TOUCHSCREEN HD CCTV TEST MONITOR

Brief Description

i) Power



ii) Accessing the Manual



The full product manual is accessible via the 'My APPS' menu via the monitor's home screen.

iii) Kit Contents



Power Supply Charger for test monitor



BNC to BNC patch lead for use with viewing video signals



12VDC 1Amp Output patch lead for camera power



RS485 Connector patch lead for testing PTZ controls

Specification

LCD	Display	New 4 inch touchscreen
Video Mode	CVBS	1 channel BNC input
	IP camera	IP Discovery/Quick ONVIF/IPC
		4K /H.265/H.264
	Coaxial HD	8 MP TVI camera, 3840 x 2160P 15 FPS
4 MP CVI camera, 2560 x 1440P 25/30 FPS		
5 MP AHD, 2560x1944P 12.5F/20F		
PTZ	RS485 control, Baud 600 -115200bps, compatible with more than 30 protocols such as PELCO	
Power In	DC12V/1amp	
PoE power output	48V PoE power output, max power 24W	
Audio test	1 channel audio signal input	
Power output	Output DC12V/3A power out	
Battery	Built-in 7.4V Lithiumpolymer battery 2400mAh (Approx. 7hr use from 5hr charge)	
Auto off	1-30 (mins)	
Working Temperature	-10°C---+50°C	
Dimension/Weight	126mm x 83mm x 33mm / 0.32kg	



A Scolmore GROUP Company

email: info@espuk.com

visit: www.espuk.com

call: 01527 51 5 150

errors & omissions excepted G18