

Product Code: A11PVDS

Description: Aperta IP PoE Single Way Outdoor Station IP65 HD with Proximity Reader



General Information

Dimensions (mm)	150 x 84 x 33
Finish	Brushed Silver
Materials	Aluminium Alloy
Mounting	Surface & Flush
Fob Reader Operating Frequency	13.56MHz
Fobs Supported	200
Warranty (Years)	3

Media Information

Camera	1.0MP CMOS Low Illumination
Video Compression	H.264
Viewing Angle (°)	110 (Horizontal)
Audio	Noise Suppression & Echo Cancellation

Programming

User Interaction	Keypad
PIN Length	6

Environment

Ingress Protection	IP65
Impact Rating (IK)	10
Operating Temperature (°C)	-10 to +50
Relative Humidity Resistance (%)	<90

Supply & Power

Operating Voltage (V DC)	15
Secondary Power Source	PoE 802.3af/at
Power Consumption (mA)	<150
Lock output	12VDC, NO & NC Contacts

Network

Network Rate (Mbps)	10/100/1000 Mbps Self-adaptive Ethernet
---------------------	---

Supplied 7 Core Cable (1m), 3 Core Cable (0.1m), 2 Core Cable (1.0m), 3 x Add/User (Dual Use) Fobs (pre-programmed), 3 x Remove/User (Dual Use) Fobs (pre-programmed), 6 x User Fobs (pre-programmed), Weather Shield & Mounting Casing, Screw & Rawl plug pack, Foam Gasket, Quick Start Guide

Features

Built-in Keypad & Fob reader for unlocking door
Audio message alerts user if the door has been unlocked

Accessories

A1IPT10: Aperta IP 13.56MHz Pack of 10 Tags