

Product Code: APDSPXMW

Description: MultiWay Video Door Station with Proximity Release



General Information

Dimensions	200mm x 87mm x 53mm
Sensor Size	1/3"
Lens size	3.6mm
Viewing Angle	70 Degrees
Audio	Full Duplex
Illumination	5 White light LEDs
Sensitivity	0.1 Lux
User Interaction	0 - 9, * and Bell
Maximum Call-able address	32
Code lengths	2 - 6
Maximum Access Codes	32 PINs, and 10,000 Tags
Reader Frequency	125KHz
Reader Effective Distance	<5cm
Recommended BUS Cable	Cat5e or higher
Weight	640g

Outputs

Lock outputs	2
Global selections	Normally Open or Normally Closed; Volt-Free or 12VDC300mA

Transmission

Protocol	BUS
Effective Distance to PSU	50m

Environment

Ingress Protection	IP55
Operating Temperature	-20°C to 40°C

Power

Operating Voltage	24VDC BUS
--------------------------	-----------

Construction

Material	Aluminium Alloy
Fixing	Surface & Flush (requires APDSKPFMS) Mounted

Accessories

EVBPSBB	12V Lock power supply with battery backup
APPOWMW	Aperta Multiway BUS power supply
APSEPMW	Aperta Multiway BUS Seperator
APMONW, APMONB, APMONWG,	Compatible Aperta Monitors
APMONBG, APAUDH, APAUDHBLK	
ENTERD	Flush Electric Lock
ENTERD-YLR	Surface Electric Lock

Component Supplied

- Fixing Screws, and Wall Plugs
- User Manual
- 10 x Access Fobs
- 3 x Green Programming add Fobs
- 3 x Red Programming removal Fobs

Additional Information

Simple 2-core Installation
High-Resolution Colour Camera
Can call addresses 1 ~ 32