



General Information

Dimensions (mm)	152 x 215 x 18
Colour	White
Materials	ABS
Mounting	Surface
Weight (Kg)	.45
Warranty (Years)	3

Media Information

Screen Size (Inches)	7
Illumination	Backlight Screen and Buttons
Resolution	800(H) x 3RGB x 480(V)
Audio	Full Duplex
Adjustments	Volume, Brightness, and Contrast Dials

Programming

User Interaction	4 buttons
Programming Type	7 x DIP switches
Maximum Settable Address	32 (set by first 5 DIP Switches)

Environment

Ingress Protection	IP20
Operating Temperature (°C)	0 to +40

Supplied Fixing Screws, and Wall Plugs, Surface Mount Bracket, User Manual

Features

Internal Call Facility

Supply & Power

Operating Voltage (V DC)	24 (BUS)
Effective Distance to PowerSupply (M)	100
Master/Slave	Yes (set by 6th DIP Switch)

Network

Recommended BUS Cable	Cat5e or higher
Communication Protocol	BUS

Accessories

APPOWSWR: Aperta Singleway BUS power supply
 APDSSW: Aperta BUS Single Way Door Station
 APDSSWKP: Aperta BUS Single Way Door Station With Keypad

Additional Information

Simple 2-core Installation
 For use with both Single way & Multiway Applications

