

Technical Specification

Product Code: BACALM66

Assistance Alarm Call Module Stainless Steel IP66 **Description:**



100 x 100 x 60
Brushed Steel
Stainless Steel & Acrylic
Surface
Blue "Halo"
0.25
2
1 - 1.5
1 x 2 Core Radial
Single Call Button

General Information

Transmission

Maximum Communication Range (m) 500 (point to point)

Inputs

Input Lines 1

Outputs

Line Outputs Single Line

Alarm Zone End of Line (Resistance)(Ω) 10k

Environment

Ingress Protection IP66

Additional Information Suitable for showers and other wet areas.

The cancel button should be mounted at between 800mm to 1000mm from the floor and should be reachable form the toilet or shower tip up seat.

There is a maximum number of 2 cancel plates on a dedicated line.

There are 5 x 20mm cable entries (top, bottom and side entry, cable entry for the rear via cutout is also provided)

Features

Compact Design BS83000 "Acknowledge" Feature High Volume Sounder Blue "Halo" Flush or Surface Mounting Braille Enhanced Cancel Button

Stainless Steel NOTE: Requires BM2/4/8, BMNET, BMNETEX, BA4ZM

The "Halo" on These Units Lights Steadily, and the Tone Double Bleeps Every 15 Seconds to Assure the Called that Help is on the Way

