

Technical Specification



Product Code: BAT7

Description: 12V - 7.0ah SLA Battery

	RECHARGEABLE VRLA BATTERY
	UL7-12 (12V 7AH/20HR)
MAINTENANCE FREE NON SPILLABLE	CONSTANT VOLTAGE CHARGE CYCLE USE: 14.4-15.0V STANDBY USE: 13.6-13.8V INITAL CURRENT: LESS THAN 2.1A
	CAUTION: DO NOT SHORT CIRCUIT DO NOT CHARGE IN A SEALED CONTAINER
WILZDATO CE	WARNING RISK OF FIRE, EXPLOSION, OR BURNS DO NOT DISASSEMBLE, HEAT ABOVE 60°C, OR INCINERAT DO NOT DISASSEMBLE, HEAT ABOVE 60°C, OR INCINERAT
	SEALED LEAD BATTERY MUST BE RECYCLED OR DISPOSED OF PROPERLY
METERS CO	www.ultracell.co.uk

General Information	
Dimensions (mm)	151 x 65 x 99
Finish	Blue & Grey
Materials	ABS
Weight (Kg)	2
Warranty (Years)	3
Supply & Power	
Operating Voltage (V DC)	12
Battery Type	Sealed Lead Acid
Consumption (Battery)(Ah)	7
Environment	
Operating Temperature (°C)	0 to +40
Features	

F1 Spade Connectors

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 E: info@espuk.com | W: espuk.com

