

Technical Specification



Product Code: CHOICE PR1SI

Description: 1 Channel Programmer with Service Interval



General Information		Outputs	
Dimensions (mr	n) 140 x 87 x 37	Relay/Contact Type	1B, Micro-Disconnection (Volt Fre
Displa	y Backlit LCD	Relay Voltage - Maximum (AC)	230
Cloc	k 12 hour am/pm, 1 minute resolution	Output Relay Resistive Load Rating (A)	2
Timing Accura	ty ±1.5 Second / Day	Output Relay Inductive Load Rating (A)	1
Materia	S Thermoplastics, Flame Retardant	Output Type	Volt Free Contact
Mountir	g Surface Only		
Heating Syste	n Pumped Only		
Warranty (Year	s) 3		
Programming			
5 5	24 Hour, 5/2 Day and 7 Day		
	Programmable		
Available Operations	2 or 3 ON/OFF Periods		
Modes Available	On, Off, Auto, All Day		
Pre-Programmed Schedule	Yes		
Summer/Winter Time Change	Yes (Automatic)		
With/without Service Interval Function	Optional Setting		
Holiday Mode	Yes		
Programme Resolution (Mins)	10		
Selectable Boost Durations	1,2 or 3 Hour Boost		
Supply & Power			
Supply Voltage (V A	C) 100 - 240		
Wiring Ty	e Fixed wiring only		
Global Selection	volt-Free; Common/Normally Open/		
	Normally Closed		
, ,	Lithium Cell CR2032		
IEC Protection Cla	SS Class II		
Environment			
Ingress Protection	IP30		
Operating Temperature (°C)	0 to +40		

24 hour, 5/2 day and 7 day Selectable 2 or 3 ON/OFF Periods Selectable 1, 2 or 3 Hour Boost Advance to Next Programmed Event Automatic Summer/Winter Time Change Standard Wall Plate - Simple Plug in and Replace Programmable Service Interval Function

Additional Information Double Insulated Construction







