

## **Technical Specification**



**Total Switch Rating** 230V AC, 2 (1) A (per channel) Output Type Switched Live Contact Type 1B, Micro-Disconnection

Product Code: CHOICE PR3n

**Description:** Choice Three channel programmer, three independent time controlled

channels. 2 individual heating zones and separate hot water control.



Outputs

General Information			
Dimensions (mn	1)	140 x 87 x 37	
Display		Backlit LCD	
Clock		12 hour am/pm, 1 minute	
		resolution	
Timing Accuracy		±1.5 Second / Day	
Materials		Thermoplastics, Flame Retardan	
Mounting		Surface Only	
Heating System		Pumped Only	
Warranty (Years	s) (	3	
Programming			
Programming Schedule	24	24 Hour, 5/2 Day and 7 Day	
		Programmable	
Available Operations	2 or 3 ON/OFF Periods		
Modes Available	On, Off, Auto, All Day		
Pre-Programmed Schedule	Yes		
Summer/Winter Time Change	Yes (Automatic)		
Holiday Mode	Yes		
Programme Resolution (Mins)	10	10	
Selectable Boost Durations	1,2	1,2 or 3 Hour Boost	
Supply & Power			
Supply Voltage (V A	2)	100 - 240	
Wiring Typ	е	Fixed wiring only	
Battery Typ	е	Lithium Cell CR2032	
IEC Protection Class		Class II	
Environment			
Ingress Protection	IP30		
Operating Temperature (°C)	0 to +40		
= : : : : :			

24 hour, 5/2 day and 7 day Selectable 2 or 3 ON/OFF Periods Selectable 1, 2 or 3 Hour Boost Advance to Next Programmed Event Automatic Summer/Winter Time Change Standard Wall Plate - Simple Plug in and Replace Pumped or Gravity System Selectable

Additional Information Double Insulated Construction









