

Product Code: CHOICE RSTAT5RF

Description: Wireless Digital Display Programmable Thermostat



Component 1

Wireless Digital Programmable Thermostat Transmitter

Quantity

1

Component 2

Wireless Thermostat Receiver

Quantity

1

General Information

Dimensions (mm)	110 x 104 x 21.5
Finish	White
Materials	ABS
Mounting	Surface or free standing
Call for Heat Indication	LCD Display
Supply & Power	
Battery Specification	AAA (x4)
Battery Low Indicator	Yes
Programming	
Adjustment Type	Comfort / Economy
Programming Schedule	24 Hour or 7 Days
Set Temperature Range (°C)	0 to 50
Temperature Display Range (°C)	5 to 35
Temperature Swing Adjustment (°C)	+/-0.5 or +0/-0.1 (Selectable)
Minimum Interval (Mins)	10
Timing Accuracy	<1 sec Per Day
Network	
Transmission Frequency (MHz)	868
Wireless Range - Open Field (m)	80
Wireless Range - Indoor (m)	30
Environment	
Ingress Protection	IP30
Operating Temperature (°C)	0 to +50
Frost Protection	Yes (5°C)

General Information

Dimensions (mm)	88 x 88 x 39.4
Finish	White
Materials	ABS
Mounting	Surface
Supply Voltage (V AC)	230
Frequency (Hz)	50
Cable Size (mm ²)	0.5- 1.5 (Flex) 0.5- 2.5 (Rigid)
Network Connection Type	Radio Frequency
Transmission Frequency (MHz)	868
Wireless Range - Open Field (m)	80
Wireless Range - Indoor (m)	30
Output Relay Rating	16A (@250V AC) Volt Free Contact
IEC Protection Class	II
Ingress Protection	IP30
Operating Temperature (°C)	0 to +50

Warranty Years 3

