

Product Code: CHPPR3B

Description: 3 Channel Programmer with Service Interval and Digital Display



General Information

Dimensions (mm)	140 x 88.6 x 32.1
Finish	Matt Black
Display	Backlit LCD
Clock	12 hour am/pm, 1 minute resolution
Timing Accuracy	±1.5 Second / Day
Materials	ABS
Heating System	Pumped Only
Warranty (Years)	3

Outputs

Number of Outputs	3
Relay Voltage - Maximum (AC)	230
Output Relay Resistive Load Rating (A)	2
Output Relay Inductive Load Rating (A)	1

Programming

Programming Schedule	24 Hour, 5/2 Day and 7 Day Programmable
Available Operations	2 or 3 ON/OFF Periods
Modes Available	On, Off, Auto, All Day
Pre-Programmed Schedule	Yes
Summer/Winter Time Change	Yes (Automatic)
With/without Service Interval Function	Optional Setting
Holiday Mode	Yes
Selectable Boost Durations	1,2 or 3 Hour Boost

Supply & Power

Supply Voltage (V AC)	230
Frequency (Hz)	50
Wiring Type	Fixed wiring only
Battery Type	Lithium Cell CR1225
IEC Protection Class	Class II

Environment

Ingress Protection	IP30
Operating Temperature (°C)	0 to +40

