

Product Code: D1010WH

Description: 3W LED IP65 Emergency Bulkhead



**General Information**

Dimensions (mm)	352 x 110 x 60
Colour	White
Materials	Polycarbonate Housing
Mounting	Ceiling or Wall
Weight (Kg)	0.6
Warranty (Years)	5

**Supply & Power**

Supply Voltage (V AC)	220 - 240
Frequency (Hz)	50
Electrical Safety	Charge & Discharge Protection
Power Consumption (W)	3

**Environment**

Ingress Protection	IP65
Operating Temperature (°C)	0 to +45
Relative Humidity Resistance (%)	<90


**Standards** BS EN 60598-2-22

**Luminaire Output**


Colour Temperature (K)	5500
Mains Luminous Flux (Lm)	120
Emergency Luminous Flux (Lm)	100
LED Lamp Type	8 x SMD 2835

**Emergency Information**

Emergency Operation	Maintained or Non-Maintained
Status Indication	Green LED
Replacement Battery	D001
Battery Specification	3.2V 1500mAh LiFePO4
Battery Duration (Hours)	3



Mains - 5500K



Emergency

**Escape Route 1 lux min**

Mounting Height	Axial/Wall		Transverse/Axial		Transverse/Wall
	Axial/Wall	Axial/Axial	Transverse/Axial	Transverse/Transverse	Transverse/Wall
2.0m	2.2	5	5.8	6.7	2.5
2.5m	2.2	5.7	6.5	7.4	2.7
3.0m	2.4	6.1	6.8	7.6	2.8

Illuminance values based on a maintenance factor of 0.8  
Photometric spacing data 1 Lux (centre to centre in metres on emergency escape routes)