

Technical Specification




Product Code: D2413WH Description: 5W LED Emergency Open Lens Downlight



General Information

General Information		Luminaire Output			
Dimensions (m	m) Ø55 x 31	Colour Temperature (K) 5500			
Emergency Module Dimensions (m	m) 180 x Ø32	Emergency Luminous Flux (Lm) 263			
Battery Dimensions (m	m) 84 x Ø41		LED Lamp Type High Power 5W LED		
Emergency Module Cutout (m	m) Ø48	Emergency Information			
Fin	sh White	Emergency Operation	Non-Maintained		
Materi	Polycarbonate Lamp Head &	Status Indication			
	Housing	Replacement Battery	D002E		
	ng Recessed	Battery Specification	3.2V 6000mAH LiFePO4		
Weight (I	0.	Battery Duration (Hours)			
Warranty (Yea	rs) 3				
Supply & Power					
Supply Voltage (V AC)	220 - 240	_			
Frequency (Hz)	50				
Electrical Safety	harge & Discharge Protection				
Power Consumption (W)	+.3				
Power Consumption (A)	0.036				
Environment					
Ingress Protection IP20		_			

Standards BS EN 60598-2-22



Escape Route 1 lux min

	Mounting Height	Axial/ Wall	Axial/ Axial	Transverse/ Axial	Transverse/ Transverse	Transverse/ Wall
	2.0m	3.1	6.9	6.9	6.9	3.0
	2.5m	3.6	8.0	8.0	8.0	3.5
	3.0m	4.0	9.1	9.1	9.1	3.9

Illuminance values based on a maintenance factor of 0.8 Photometric spacing data 1 Lux (centre to centre in metres on emergency escape routes)

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 E: info@espuk.com | W: espuk.com

0 48m ole Cut UK CA CE IP20

Page 1 of 1 (22/08/23) Errors & Omissions excluded Specification is subject to change without notice