

Product Code: ECSPK5

Description: Smart Security Alarm Kit with Hub, Pet PIR, Door Contact and Remote Fob



Component 1

ECSPHB - Smart Alarm Hub with Battery Backup

Quantity

1

Component 2

ECSPPET - Smart Security Pet PIR

Quantity

1

General Information

Dimensions (mm)	109.5 x 109.5 x 40
Finish	White
Materials	ABS
Mounting	Surface
Available Operations	Home/Arm/Disarm/SOS
Sounder Output (dB)	95
Maximum Devices	32
Transmission frequency (MHz)	433
Weight (Kg)	0.25

Supply & Power

Operating Voltage (V DC)	12
Power Consumption (A)	1
Battery Specification	7.4V 600mAh Lithium Polymer
Power Reserve	8 Hours (Approx.)

Transmission

Router Transmission Frequency (GHz)	2.4 (IEEE 802.11 b/g/n)
Router Transmission Range (m)	150

Auxiliary

GSM	Yes (Full-size SIM Card)
GSM Frequency (MHz)	850, 900, 1800 & 1900

Environment

Operating Temperature (°C)	-10 to 55
Relative Humidity Resistance (%)	<80 (non-condensing)

General Information

Dimensions (mm)	107 x 53 x 32
Bracket Dimensions (mm)	52 x 30 x 26.5
Finish	White
Mounting	Surface
PIR Range (m)	8
Number of PIRs	2
Transmission frequency (MHz)	433
Minimum Detectable Object Weight (Kg)	>25
Operating Voltage (V DC)	3
Power Consumption (A)	0.0095
Battery Type	AA (LR06) x 3
Power Reserve	12 Months (Approx.)
Zone Types	Normal Sensor/24h mode/Delay mode/ Home mode/24h mute sensor/Home delay mode
Operating Temperature (°C)	-10 to 55
Relative Humidity Resistance (%)	<80 (non-condensing)
Weight (Kg)	0.046

Product Code: ECSPK5

Description: Smart Security Alarm Kit with Hub, Pet PIR, Door Contact and Remote Fob

Component 3		Quantity	Component 4		Quantity
ECSPCT - Smart Door / Window Contact Sensor		1	ECSPRC - Smart Alarm Remote Control		1
General Information			General Information		
Dimensions (mm)	55.7 x 30.3 x 16		Dimensions (mm)	57 x 31 x 11	
Finish	White		Finish	Black	
Materials	ABS		Materials	ABS	
Mounting	Surface		Available Operations	Home/Arm/Disarm/SOS	
Magnet Dimensions (mm)	25 x 10 x 9		Transmission frequency (MHz)	433	
Transmission frequency (MHz)	433		Operating Voltage (V DC)	3	
Operating Voltage (V DC)	3		Battery Type	CR 2025	
Power Consumption (A)	0.015		Power Consumption (mA)	<7	
Battery Type	CR2477		Power Reserve	12 Months (Approx.)	
Power Reserve	12 Months (Approx.)		Operating Temperature (°C)	-10 to 55	
Zone Types	Normal Sensor/24h mode/Delay mode/Home mode/24h mute sensor/Home delay mode		Relative Humidity Resistance (%)	<80 (non-condensing)	
Operating Temperature (°C)	-10 to 55		Weight (Kg)	0.02	
Relative Humidity Resistance (%)	<80 (non-condensing)				
Weight (Kg)	0.2				
Warranty Years 1					
Supplied	Fort Hub Fort Pet PIR Fort Door/Window Contact Fort Remote Control AC Adapter Product Batteries Mounting Screws & Wall plugs User Guides				