

Technical Specification



Description: LED 2W Maintained Exit Sign Legend RIGHT





General Information		Luminaire Output		
Dimensions (mm) 305 x 190 x 225	Colour 7	Temperature (K)	5500
Mate	rials Polycarbonate frame with legend	Mains Lum	inous Flux (Lm)	60
Mounting Ceiling or Wall		Emergency Lum	inous Flux (Lm)	44
Weight (Kg) 0.8			LED Lamp Type	16 x SMD 2835
Warranty (Years) 3		Emergency Information		
Supply & Power		Emergency Operation	Maintained or Non-Maintained	
Supply Voltage (V AC)	220 - 240	Status Indication	Green LED	
Frequency (Hz)	50	Viewing Distance (m)	24	
Electrical Safety	Charge & Discharge Protection	Battery Specification	3.6V 900mAh Ni-Cd	
Power Consumption (W)	3	Battery Duration (Hours)	3	
Power Consumption (A)	0.019			
Environment				
Ingress Protection	IP20			
Operating Temperature (°C)	0 to +60			
Relative Humidity Resistance (%)	95 (Max.)			
	IBAT3.6V900: 3.6V 900mAh Battery IWMBEXHSIGN: Hanging Sign Wall Bracket			
Features Do	uble Sided			
Hinge Rotates 90 Degrees				
Standards BS	EN 60598-2-22			

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com



Page 1 of 1 (18/10/22) Errors & Omissions excluded. Specification is subject to change without notice.