

Product Code: EZT3KB

Description: Single Internal Door Proximity Keypad Kit c/w Flush Exit Button & Internal Green Callpoint



Supplied

- 1 x EZTAG3B
- 1 x EVBPSBB
- 1 x A1EXIT
- 1 x A1ECP
- 1 x A1ML250

Component 1

EZTAGB - Proximity & Keypad Door Entry

Quantity

1

Component 2

EVBPSBB - Power Supply Unit with Battery Backup

Quantity

1

General Information	
Dimensions (mm)	150 x 44 x 24
Finish	Black
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	<50
PIN length	2 - 6 Digits
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlight	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

Supply & Power	
Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

Inputs & Outputs	
Relay Types	Normally Open & Normally Closed; Volt-Free

Environment	
Ingress Protection	IP65

Component 3

A1EXIT - Flush Push to Exit Release Button

Quantity

1

Component 4

A1ECP - Green Internal Emergency Call Point

Quantity

1

General Information	
Dimensions (mm)	86 x 86 x 22
Finish	Brushed Steel
Materials	Stainless Steel
Mounting	Surface or Flush (Backbox not Included)
Relay Voltage	125-250V
Contact Type	2 x SPST (Normally Open & Normally Closed)
Output Relay Rating	3A @125-250V AC
Operating Temperature (°C)	-20 to +55

General Information	
Dimensions (mm)	87.5 x 87.5 x 32
Finish	Green (RAL6016)
Materials	Fire Resistant ABS
Mounting	Surface or Flush (Backbox Included)
Contact Type	Double Pole Double Throw
Output Relay Rating	3A @125-250V AC
Operating Temperature (°C)	-20 to +55
Weight (Kg)	0.17



Product Code: EZT3KB

Description: Single Internal Door Proximity Keypad Kit c/w Flush Exit Button & Internal Green Callpoint

Component 5	Quantity
A1ML250 - Internal 250kg Holding Force Magnetic Lock with Z and L Brackets	1

General Information	
Dimensions (mm)	48 x 250 x 27
Finish	Brushed Silver
Materials	Aluminium Alloy
Mounting	Surface Only
Maximum Holding Force (Kg)	250
Operating Voltage (V DC)	12 & 24
Operating Temperature (°C)	-20 to +50

