

**Product Code:** EZT3KXTB

**Description:** Single External Door Proximity Keypad Kit c/w IP55 Mushroom Exit Button



### Supplied

- 1 x EZTAG3B
- 1 x EVBPSBB
- 1 x EVEXITMIP55
- 1 x EVBGEEXT2
- 1 x A1ML300XT

### Component 1

EZTAGB - Proximity & Keypad Door Entry

### Quantity

1

### Component 2

EVBPSBB - Power Supply Unit with Battery Backup

### Quantity

1

#### General Information

Dimensions (mm)	150 x 44 x 24
Finish	Black
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	<50
PIN length	2 - 6 Digits
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlight	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

#### Supply & Power

Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

#### Inputs & Outputs

Relay Types	Normally Open & Normally Closed; Volt-Free
-------------	--

#### Environment

Ingress Protection	IP65
--------------------	------

#### General Information

Dimensions (mm)	129 x 73 x 50
Materials	ABS
Mounting	Surface Only
Supply Voltage (V AC)	100 - 230
Output Type	Configurable Normally Open or Normally Closed
Number of Outputs	Configurable Normally Open or Normally Closed2 (1 xSwitched & 1 xConstant)
Lock output	12V DC @ 1.5A
Ingress Protection	IP20
Operating Temperature (°C)	0 to +50

### Component 3

EVEXITMIP55 - Push to Exit Mushroom Release Button IP55

### Quantity

1

### Component 4

EVBGEEXT2 - IP67 Surface Green Emergency Resettable Call Point

### Quantity

1

#### General Information

Dimensions (mm)	85 x 80 x 85
Materials	ABS
Mounting	Surface Only
Relay Voltage	30V
Contact Type	Normally Open & Normally Closed
Output Type	Clean Contact
Ingress Protection	IP55
Operating Temperature (°C)	0 to +50
Weight (Kg)	0.2

#### General Information

Dimensions (mm)	89 x 89 x 72
Finish	Green
Materials	Polycarbonate
Mounting	Surface Only
Maximum Cable Size (mm <sup>2</sup> )	2.5
Contact Type	Double Pole Double Throw
Output Relay Rating	3A (12 to 24V DC & 125 to 250V AC)
Ingress Protection	IP67
Operating Temperature (°C)	-25 to +65
Weight (Kg)	0.282





Component 5	Quantity
A1ML300XT - External 300kg Holding Force Magnetic Lock with Z and L Brackets	1

General Information	
Dimensions (mm)	47 x 220 x 28
Finish	Brushed Silver
Materials	Aluminium Alloy
Mounting	Surface Only
Maximum Holding Force (Kg)	300
Operating Voltage (V DC)	12 & 24
Ingress Protection	IP68
Operating Temperature (°C)	-20 to +50

