

**Product Code:** EZTAG3PROB

**Description:** Proximity and Keypad Door Entry Kit



**Component 1**

EZTAGB - Proximity & Keypad Door Entry

**Quantity**

1

**Component 2**

EV-EXIT - Push to Exit Release Button

**Quantity**

1

**General Information**

Dimensions (mm)	150 x 44 x 24
Finish	Black
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	< 50
PIN length	2 - 6 Digits
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlight	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

**Supply & Power**

Supply Voltage (V AC)	12 - 24
Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

**Inputs & Outputs**

Relay Types	Normally Open & Normally Closed; Volt-Free
-------------	--

**Environment**

Ingress Protection	IP65
--------------------	------

**General Information**

Dimensions (mm)	87.5 x 87.5 x 22
Materials	Stainless Steel
Mounting	Surface & Flush (requires UDTASMBSS Mounted)
Maximum Cable Size (mm <sup>2</sup> )	2.5
Relay Voltage	30V
Contact Type	Normally Open
Output Type	Clean Contact
Ingress Protection	IP20
Operating Temperature (°C)	-20 to 55
Weight (Kg)	0.17

**Component 3**

EV-EBG - Internal Call Point Door Release

**Quantity**

1

**Component 4**

EV-ML-250 - Electromagnetic Lock

**Quantity**

1

**General Information**

Dimensions (mm)	87.5 x 87.5 x 57.5
Finish	Green (RAL6016)
Materials	ABS
Mounting	Surface
Maximum Switchable Voltage	30V DC @ 2A
Output Type	Clean Contact
Number of Outputs	4 (2 Normally Open & 2 Normally Closed)
Ingress Protection	IP24D
Operating Temperature (°C)	-20 to 55
Weight (Kg)	0.16

**General Information**

Dimensions (mm)	250 x 42 x 25 (Electro-Magnet)
Armature Dimensions (mm)	180 x 38 x 10
Materials	Stainless Steel
Mounting	Surface Only
Monitored/Un-Monitored	Un-Monitored
Maximum Holding Force (Kg)	250
Maximum Holding Force (lb)	550
Operating Voltage (V DC)	12 & 24
Maximum Cable Size (mm <sup>2</sup> )	2.5
Power Consumption (mA)	420
Ingress Protection	IP20
Operating Temperature (°C)	-20 to 55



**Product Code:** EZTAG3PROB

**Description:** Proximity and Keypad Door Entry Kit

<b>Component 5</b>	<b>Quantity</b>
EVBPSBB - Power Supply Unit with Battery Backup	1

<b>Component 6</b>	<b>Quantity</b>
EZT3ST10 - Proximity Fobs	10

General Information	
Dimensions (mm)	129 x 73 x 50
Materials	ABS
Mounting	Surface
Supply Voltage (V AC)	100 - 230
Input Type	Coil
Activation Type	Energise with a Normally Open Clean contact
Constant Output	12V @ 1A
Output Type	Configurable Normally Open or Normally Closed
Number of Outputs	2 (1 xSwitched & 1 xConstant)
Lock output	12V DC @ 1.5A
Ingress Protection	IP20

General Information	
Finish	Blue
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	<50

**Supplied** Keypad and Mounting Bracket  
Screws and Wall Plugs  
Diode and Capacitor  
User Manual  
10 x fobs

Accessories
EVBPSBB: 12V Lock power supply with battery backup
EV-EXIT: Push to Exit Release Button
EVEXITC: Contactless Exit button
EVEXITM: Push to Exit Mushroom Release Button
EXEVITMIP55: Push to Exit Mushroom Release Button IP55
EV-EBG: Green Emergency Break Glass
EXEBGEXT: External Emergency Break Glass
ENTERD: Flush Electronic Lock
ENTERD-YLR: Surface Electronic Lock
EV-ML-250: Electromagnetic Lock
EV-ML-500XT:

