

Product Code: EZTAG3PROEXT

Description: Proximity and Keypad External Door Entry Kit



Component 1

EZTAGB - Proximity & Keypad Door Entry

Quantity

1

Component 2

EV-EXIT - Push to Exit Release Button

Quantity

1

General Information

Dimensions (mm)	150 x 44 x 24
Finish	Black
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	<50
PIN length	2 - 6 Digits
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlight	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

Supply & Power

Supply Voltage (V AC)	12 - 24
Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

Inputs & Outputs

Relay Types	Normally Open & Normally Closed; Volt-Free
-------------	--

Environment

Ingress Protection	IP65
--------------------	------

General Information

Dimensions (mm)	87.5 x 87.5 x 22
Materials	Stainless Steel
Mounting	Surface & Flush (requires UDTASMBSS Mounted)
Maximum Cable Size (mm²)	2.5
Relay Voltage	30V
Contact Type	Normally Open
Output Type	Clean Contact
Ingress Protection	IP20
Operating Temperature (°C)	-20 to 55
Weight (Kg)	0.17

Component 3

EVEBGEXT2 - IP67 Surface Green Emergency Resettable Call Point

Quantity

1

Component 4

EV-ML-250 - Electromagnetic Lock

Quantity

1

General Information

Dimensions (mm)	89 x 89 x 72
Finish	Green
Materials	Polycarbonate
Mounting	Surface Only
Output Type	Clean Contact
Ingress Protection	IP67
Operating Temperature (°C)	-25 to +65
Weight (Kg)	0.282

General Information

Dimensions (mm)	250 x 42 x 25 (Electro-Magnet)
Armature Dimensions (mm)	180 x 38 x 10
Materials	Stainless Steel
Mounting	Surface Only
Monitored/Un-Monitored	Un-Monitored
Maximum Holding Force (Kg)	250
Maximum Holding Force (lb)	550
Operating Voltage (V DC)	12 & 24
Maximum Cable Size (mm²)	2.5
Power Consumption (mA)	420
Ingress Protection	IP20
Operating Temperature (°C)	-20 to 55



Product Code: EZTAG3PROEXT

Description: Proximity and Keypad External Door Entry Kit

Component 5	Quantity
EVBPSBB - Power Supply Unit with Battery Backup	1

Component 6	Quantity
EZT3ST10 - Proximity Fobs	10

General Information	
Dimensions (mm)	129 x 73 x 50
Materials	ABS
Mounting	Surface
Supply Voltage (V AC)	100 - 230
Input Type	Coil
Activation Type	Energise with a Normally Open Clean contact
Constant Output	12V @ 1A
Output Type	Configurable Normally Open or Normally Closed
Number of Outputs	2 (1 xSwitched & 1 xConstant)
Lock output	12V DC @ 1.5A
Ingress Protection	IP20

General Information	
Finish	Blue
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	<50

Supplied Keypad and Mounting Bracket
Screws and Wall Plugs
Diode and Capacitor
User Manual
10 x fobs

Accessories
EVBPSBB: 12V Lock power supply with battery backup
EV-EXIT: Push to Exit Release Button
EVEXITC: Contactless Exit button
EVEXITM: Push to Exit Mushroom Release Button
EXEVTMIP55: Push to Exit Mushroom Release Button IP55
EV-EBG: Green Emergency Break Glass
EXEBGEXT: External Emergency Break Glass
ENTERD: Flush Electronic Lock
ENTERD-YLR: Surface Electronic Lock
EV-ML-250: Electromagnetic Lock
EV-ML-500XT:

