

**Product Code:** EZTAG3PROMF

**Description:** Proximity, Keypad, Door Entry with Mushroom Button and Foot-Pull Kit



**Component 1**

EZTAG3 - Proximity & Keypad Door Entry

**Quantity**

1

**Component 2**

EVEXITM - Push to Exit Mushroom Release Button

**Quantity**

1

**General Information**

Dimensions (mm)	150 x 44 x 24
Finish	Silver
Materials	Aluminium
Mounting	Surface
Fob Reader Operating Frequency (KHz)	125
Fob Reader Operating Distance (mm)	< 50
PIN length	2 - 6 Digits
Maximum Capacity	Zone 1; 1000 Fob/PIN Zone 2; 10 Fob/PIN
Backlight	Keys; Blue LEDs
Tamper Facility	Yes
Status Indication	Red, Green, and Amber LEDs

**Supply & Power**

Supply Voltage (V AC)	12 - 24
Operating Voltage (V DC)	12 - 24
Operating Current (mA)	110
Unlatched Relay Time	1 - 99 Seconds
Maximum Switchable Load	30V @ 4A
Operation Type	Latched & Unlatched
Lock outputs	2

**Inputs & Outputs**

Relay Types	Normally Open & Normally Closed; Volt-Free
-------------	--

**Environment**

Ingress Protection	IP65
--------------------	------

**General Information**

Dimensions (mm)	87.5 x 87.5 x 35
Materials	Stainless Steel Fascia & ABS Button
Mounting	Surface & Flush (requires UDTASMBSS) Mounted
Maximum Cable Size (mm <sup>2</sup> )	2.5
Relay Voltage	30V
Contact Type	Normally Open & Normally Closed
Output Type	Clean Contact
Ingress Protection	IP20
Weight (Kg)	0.173

**Component 3**

EV-EBG - Internal Call Point Door Release

**Quantity**

1

**Component 4**

EV-ML-250 - Electromagnetic Lock

**Quantity**

1

**General Information**

Dimensions (mm)	87.5 x 87.5 x 57.5
Finish	Green (RAL6016)
Materials	ABS
Mounting	Surface
Maximum Switchable Voltage	30V DC @ 2A
Output Type	Clean Contact
Number of Outputs	4 (2 Normally Open & 2 Normally Closed)
Ingress Protection	IP24D
Operating Temperature (°C)	-20 to 55
Weight (Kg)	0.16

**General Information**

Dimensions (mm)	250 x 42 x 25 (Electro-Magnet)
Armature Dimensions (mm)	180 x 38 x 10
Materials	Stainless Steel
Mounting	Surface Only
Monitored/Un-Monitored	Un-Monitored
Maximum Holding Force (Kg)	250
Maximum Holding Force (lb)	550
Operating Voltage (V DC)	12 & 24
Maximum Cable Size (mm <sup>2</sup> )	2.5
Power Consumption (mA)	420
Ingress Protection	IP20
Operating Temperature (°C)	-20 to 55



**Product Code:** EZTAG3PROMF

**Description:** Proximity, Keypad, Door Entry with Mushroom Button and Foot-Pull Kit

<b>Component 5</b>	<b>Quantity</b>
EVBPSBB - Power Supply Unit with Battery Backup	1

General Information	
<b>Dimensions (mm)</b>	129 x 73 x 50
<b>Materials</b>	ABS
<b>Mounting</b>	Surface
<b>Supply Voltage (V AC)</b>	100 - 230
<b>Input Type</b>	Coil
<b>Activation Type</b>	Energise with a Normally Open Clean contact
<b>Constant Output</b>	12V @ 1A
<b>Output Type</b>	Configurable Normally Open or Normally Closed
<b>Number of Outputs</b>	2 (1 xSwitched & 1 xConstant)
<b>Lock output</b>	12V DC @ 1.5A
<b>Ingress Protection</b>	IP20

<b>Component 6</b>	<b>Quantity</b>
EVFOOT - Stainless Steel Door Pull	1

General Information	
<b>Dimensions (mm)</b>	125 x 75
<b>Finish</b>	Brushed
<b>Materials</b>	Stainless Steel

<b>Component 7</b>	<b>Quantity</b>
EZT3ST10 - Proximity Fobs	10

General Information	
<b>Finish</b>	Blue
<b>Fob Reader Operating Frequency (KHz)</b>	125
<b>Fob Reader Operating Distance (mm)</b>	<50

**Supplied** Keypad and Mounting Bracket  
Screws and Wall Plugs  
Diode and Capacitor  
User Manual  
10 x fobs

### Accessories

EVBPSSBB: 12V Lock power supply with battery backup  
EV-EXIT: Push to Exit Release Button  
EVEXITC: Contactless Exit button  
EVEXITM: Push to Exit Mushroom Release Button  
EXEVITMIP55: Push to Exit Mushroom Release Button IP55  
EV-EBG: Green Emergency Break Glass  
EXEBGEXT: External Emergency Break Glass  
ENTERD: Flush Electronic Lock  
ENTERD-YLR: Surface Electronic Lock  
EV-ML-250: Electromagnetic Lock  
EV-ML-500XT:

