

## **Technical Specification**



Product Code: H512VDW

Description: HDview IP PoE Varifocal 2.8-12mm Motorised Lens Dome Camera White



General Information		Recording
Dimensions (mm) 129	x 110 x 129	Storage Type Micro SD, up to 256 GB
Finish Whi	te & Black	Environment
<b>Materials</b> Met	al	Ingress Protection IP67
Mounting Surf	ace	Ü
Weight (Kg) 0.66		
Warranty (Years) 3		
Supply & Power		
Operating Voltage (V DC) 12		
Power Consumption (W) 7.5		
Other Power Sources Po	E (IEEE802.3af)	
Media Information		
Effective Pixels	5MP (2880 x 1620)	
Sensor Size (*)	1/2.7" Progressive CMOS	
Lens size (mm)	2.8-12	
Lens Type	Varifocal (Motorised)	
Viewing Angle (°)	96.4 - 32.7	
Electronic Shutter Type	Auto / Manual	
Speed (sec/°)	1 to 1/100000	
Scanning System	Progressive Scan CMOS	
Frames Per Second (FPS)	5MP (2880*1620), Max 25fps	
	4MP (2560*1440), Max 25fps	
	3MP (2304*1296), Max 30fps	
	1080P (1920*1080), Max 30fps	
Maximum IR Distance (m)		
IR Wavelength (nm)		
	128 Kbps - 6 Mbps	
Microphone Supported		
, ,	IR-Cut filter with Auto Switch (IC	
Basic Detection	Cross line, intrusion(based on hi alarm, Audio Detection	uman body detection), Motion Detection, Ultra Motion Detection, Tampering
Intelligent Detection	Watermark, IP Address Filtering HTTP authentication	r, Access Policy, ARP Protection, RTSP Authentication, User Authentication,
Network		
Interface	1 RJ45; 10/100M Base-TX Ether	rnet
ONVIF Compliant	Yes; Profile S, Profile G, Profile T	
Network Functions	IPv4, IPv6 ,IGMP, ICMP, ARP, TCF SMTP, SNMP, QoS, RTMP,SSL/TI	D, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, LS

**Supplied** Quick Start Guide, Mounting Guide, Installation Screws and Rawlplugs and Pass Through Gland

**Compatible Products** Compatible with the range of 24/7 Network Video Recorders (NVR) 4, 8, 16, 32 and 64 Channels

## Accessories

DBW4: HDview IP 5MP Dome Deep Base White



