

Technical Specification

Product Code: HC528FBG

Description: 2.8mm Fixed Lens HDview Bullet Camera - Grey







Dimensions (mm)	74 x 75 x 191	Storage Type Micro SD, up to 256 GB	
Finish	Grey	eSATA Connection 1 RJ45; 10/100M Base-TX Ethernet	
Materials	Metal	Environment	
Weight (Kg)	0.50	Ingress Protection IP67	
Warranty (Years)	3	Operating Temperature (°C) -30 to +60	
Supply & Power		Storage Temperature (°C) -30 to +60	
Operating Voltage (V DC)	12		
Power Consumption (W)			
Other Power Sources	PoE (IEEE802.3af)		
Media Information			
	xels 2880 x 1620 (5MP)		
	e (") 1/2.7" Progressive CMOS		
Lens size (r			
,	iype Fixed		
	e (°) 112.9 (H), 59.1 (V), 121.2 (D)		
Auto Electronic Shutte			
Speed (se	ec/°) 1 to 1/100000		
Scanning Sys	tem Progressive Scan CMOS		
Frames Per Second (F	PS) 30 (@5MP 2880 x 1620)		
Maximum IR Distance			
IR Wavelength (,		
	Rate 128 Kbps - 16 Mbps		
Microphone Suppo			
Speaker Suppo			
White Light Range			
	ight IR-Cut filter with Auto Switch		
	tion Motion Detection, Tampering	<u>'</u>	
	Region Exit Detection	-	
Reset	Key No		
Network			
Interf	ace 1 RJ45; 10/100M Base-TX Et	hernet	
ONVIF Compl	iant Yes; Profile S, Profile G, Profi	Yes; Profile S, Profile G, Profile T	
Network Function	ONS IPv4, IGMP, ICMP, ARP, TCP, U HTTPS, SMTP, 802.1x, SNMF	JDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, P, QoS, RTMP, SSH	
Supplied Quick Sta	art Guide, Mounting Guide, Installa	tion Screws and Rawlplugs and Pass Through Gland	

Accessories

BBG1: HDVIEW IP 24/7 Bullet Deep Base - Grey







