

**Product Code:** HC528FBW

**Description:** 2.8mm Fixed Lens HDview Bullet Camera - White



### General Information

Dimensions (mm)	74 x 75 x 191
Finish	White
Materials	Metal
Weight (Kg)	0.50
Warranty (Years)	3

### Supply & Power

Operating Voltage (V DC)	12
Power Consumption (W)	<11.5
Other Power Sources	PoE (IEEE802.3af)

### Recording

Storage Type	Micro SD, up to 256 GB
eSATA Connection	1 RJ45; 10/100M Base-TX Ethernet

### Environment

Ingress Protection	IP67
Operating Temperature (°C)	-30 to +60
Storage Temperature (°C)	-30 to +60

### Media Information

Effective Pixels	2880 x 1620 (5MP)
Sensor Size (")	1/2.7" Progressive CMOS
Lens size (mm)	2.8
Lens Type	Fixed
Viewing Angle (°)	112.9 (H), 59.1 (V), 121.2 (D)
Auto Electronic Shutter (s)	Auto / Manual
Speed (sec/°)	1 to 1/100000
Scanning System	Progressive Scan CMOS
Frames Per Second (FPS)	30 (@5MP 2880 x 1620)
Maximum IR Distance (m)	30
IR Wavelength (nm)	850
Video Bit Rate	128 Kbps - 16 Mbps
Microphone Supported	Built-in
Speaker Supported	Built-in
White Light Range (m)	30
Day/Night	IR-Cut filter with Auto Switch (ICR)
Basic Detection	Motion Detection, Tampering Alarm, Audio Detection
Intelligent Detection	Support False Alarm Filtering, Line Crossing Detection, Intrusion Detection, Region Entrance Detection, Region Exit Detection
Reset Key	No

### Network

Interface	1 RJ45; 10/100M Base-TX Ethernet
ONVIF Compliant	Yes; Profile S, Profile G, Profile T
Network Functions	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSH

**Supplied** Quick Start Guide, Mounting Guide, Installation Screws and Rawplugs and Pass Through Gland

**Compatible Products** Compatible with the range of 24/7 Network Video Recorders (NVR) 4, 8, 16, 32 and 64 Channels

### Accessories

BBW1: HDVIEW IP 24/7 Bullet Deep Base - White

