

Technical Specification

Product Code: HDVIP132R12TB

Description: HDview IP PoE 5MP 32CH NVR 12TB





General Information	Reco		do Tarabata
Dimensions (mm) 380	< 340 x 50	Maximum Capacity	
Warranty (Years) 3		Ctorogo Tuno	8 Terabytes per SATA connection
Supply & Power		Storage Type Internal HDD	SATA Hard Disk Drive
Operating Voltage (V AC) 11			
Power Consumption (mA) <1	2W	SATA Connection(s)	
Inputs & Outputs			8MP, 5MP, 3MP, 1080p, 720p Manual, Schedule, Alarm
Alarm Inputs 16			Manual, Scriedule, Alarm
Alarm Outputs 1		onment	##N
Video Input Channels 32:		Operating Temperature	e (°C) -10 to +50
16 (F	,		
,	igital)		
Audio Output Channels (RCA) 1			
Media Information			
Frames Per Second (FPS)	240 @1080p, 120 @4MP	<u> </u>	
Display Video Output	k HDMI, 1 x VGA		
Display Split	1, 4, 6, 8, 9, 10, 10-1, 12, 13, 13-1, 14, 16, 17, 19, 20, 22, 25, 32 & 36		
Display Resolutions	HDMI 1 (Full GUI): 1024x768, 1280x720, 1280x1024, 1440x900, 1920x1080, 3840x2160/EDID		
	HDMI 2 (Limited GUI): 1024x768, 1280x7		
	VGA (Full GUI): 1024x768, 1280x720, 128	30x1024, 1440x900, 1920)x1080
	Maximum 16 Channels		
·	Network USB2.0 (Up to 32GB Storage Medium Supported)		
Hardware Reset	Yes (Via Password Reset)		
Network			
Interface			
	1 x USB 2.0 (Front), 1 x USB 3.0		
	1 x USB 2.0 (Rear)		
Network Connection	1 x RS485		
	Mobile app, Windows & Mac Client, Web Interface		
Network Monitoring	wiobile app, willidows & wac client, web	IIILEITACE	
Supplied 1 x USB Mous	se (0.5m), 1 x C13 IEC Cable (0.5m), 1 x Et	hernet Cable (0.5m)	
		, ,	
Compatible Products HDVIPC: Ran			
REKIP: Range			
	5" LED CCTV Monitor		
	5" LED CCTV Monitor		
MON23L: 23.	3" LED CCTV Monitor		
	.5" LED 4K CCTV Monitor		

Slow Forward (1/2x, 1/4x, 1/8x, 1/16x)

Accessories

Feature

Additional Information Playback Function: Fast Forward & Reverse (2x, 4x, 8x, 16x)

HDVIP1632RRMB: Rack Mount Bracket IPIN1POE: 1 Channel POE Injector IPSW4POE: 4 Channel POE Switch IPSW8POE: 8 Channel POE Switch

Premium Surveillance Hard Disk Drive pre-installed

