

Technical Specification



Product Code: MAGDUO2B

Description: 2 Zone 2-Wire Fire Alarm Panel (Black)



General Information

Dimensions (mm)	331 x 331 x 99			
Finish	Black			
Materials	V0 rated ABS			
Maximum Detectors Per Zone	Up to 32 Devices (Dependant on Device Loading Units, 160 per Zone)			
Sounders and Detectors Mixed on Zones	Yes			
Maximum Cable Length Per Zone (m)	500			
Weight (Kg)	2.25Kg			
Warranty (Years)	3			
O				

Iominal 700mA)
Core Screened Fire Rated Cable)
V 3.2 Ah SLA Battery (Sold Seperately)
Conventional

Inputs & Outputs

inputs & Outputs				
Programmable Inputs	2; 3.3 Volts @ 10mA (Un-Monitored)			
Zones	2; Up to 32 Devices (Dependant on Device Loading Units, 160 per Zone)			
Maximum Devices Per Zone	Up to 32 Devices (Dependant on Device Loading Units, 160 per Zone)			
Auxiliary Output	24V DC @ 250mA			
Output Zones	2 (Up to 32 Devices (Dependant on Device Loading Units , 160 per Zone))			
Monitored Outputs	2			
Monitored Output Ratings	Rated at 28V DC @ 250mA each			
Unmonitored Outputs	2			
Unmonitored Output Ratings	Fire & fault; 30V DC @ 1A each			
2 Monitored Outputs	Rated at 28VDC @ 250mA each			
2 Un-Monitored Outputs	Fire & fault; 30VDC @ 1A each			

Environment

	Operatir	ng Temperature (°C)	+5 to +40		
Supplied	2 x Battery leads (1 x f	Red, 1 x Black), 1 x B	attery connecting Lead,	1 x 315mA quickblow fuse,	2 x panel keys, 2 x 680

Ingress Protection IP30

Supplied 2 x Battery leads (1 x Red, 1 x Black), 1 x Battery connecting Lead, 1 x 315mA quickblow fuse, 2 x panel keys, 2 x 680 Ohm resistor, 2 x 10K ohm Resistor, 2 x 3.275K Ohm Resistors

Standards BS EN 54-2, BS EN 54-4

Accessories

BAT32: 12V 3.2Ah SLA Battery MAGDUOPK: 2 MAGDUO Panel Keys MAGDUOPCPS: MAGDUO Software

MAGDUOBBB: Battery Expansion Box for MAGDUO

