

Product Code: MAGPRO-CP

Addressable Call Point

Description:

Technical Specification





General Information	
Dimensions (mm)	90 x 90 x 57
Finish	Red
Mounting	Surface or Flush (Surface Back Box Supplied)
Type of the frangible element	A
Weight (Kg)	0.175
Warranty (Years)	3
Supply & Power	
Operating Voltage (V DC)	15 - 32
Cable Size (mm ²)	0.4 - 2.0
Consumption Without Communication (μ A)	125 (@27V DC)
Consumption With Communication (μ A)	160 (@27V DC)
Consumption in Fire Mode (mA)	3
Wiring Type	Analogue Addressable (MAGPRO)
Communication	
Protocol Type	Custom (Closed)
Environment	
Ingress Protection	IP40
Operating Temperature (°C)	-10 to +60
Relative Humidity Resistance (%)	93 (±3) (@40°C)
Compatible Products Compatible with MAGPRO16, MAGPRO16G, MAGPRO96 and MAGPRO96G	
Standards BS EN 54-11, BS EN 54-17	
Accessories	

Accessories

MAGPRO-CPC: Pack of 5 Call Point Covers MAGPRO-PROG: Address Programming Tool For MAGPRO Devices

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com



Page 1 of 1 (18/10/22) Errors & Omissions excluded. Specification is subject to change without notice.