

Product Code: MAGPRO96

Description: Addressable 96 Zone Fire Panel



### General Information

<b>Protocol Type</b>	Custom (Closed)
<b>Wire Gauge</b>	Up to 1.5mm
<b>Loops</b>	Up To 4
<b>Zones</b>	16 Per Loop
<b>Maximum Number of events in Log</b>	10240
<b>Dimensions (Metal Casing)</b>	441 x 331 x 80 mm
<b>Dimensions (Front Cover)</b>	461 x 344 x 45 mm
<b>Weight</b>	6kg

### Inputs

<b>Max Devices per Loop</b>	Up to 250 Devices (Loop Calculation Required)
<b>Maximum number of Loops</b>	Expandable up to 2

### Outputs

<b>Monitored Outputs</b>	4
<b>Un-Monitored Outputs</b>	4 (240VAC @ 10A)
<b>Auxiliary Output</b>	24VDC @ 300mA

### Power

<b>Operating Voltage</b>	230 VAC ± 10% 50/60Hz
<b>PSU Output</b>	7A
<b>Standby Supply</b>	Up to 12V 17Ah (Battery Calculation Required)

### Environment

<b>Operating Temperature</b>	-5°C to 50°C
------------------------------	--------------

### Accessories

<b>MAGDUOPK</b>	Pack of 2 Keys
<b>BAT18</b>	12V 17Ah SLA Battery
<b>MAGPRO-PROG</b>	Address Programming Tool For MAGPRO Devices
<b>MAGPRO96-L250</b>	Single Loop Expander for 250 Devices
<b>MAGPRO-NIC</b>	Network Interface Card

### Components Supplied

- 2 x 10k Ohm Resistors
- 1 x 2A Quick-Blow Fuse