

Product Code: MAGPRO96

Description: Addressable 96 Zone Fire Panel



General Information

Dimensions (mm)	430 x 330 x 117
Maximum Number of Events in Log	10000
Volume Modes	2 (Low & High)
Device Loading Units (DLU's) - Low	13
Weight (Kg)	6
Warranty (Years)	3

Supply & Power

Operating Voltage (Mains Powered Panel)(V DC)	25.5 - 35
Operating Voltage (Battery Powered Panel)(V DC)	23 - 26
Standby Supply	Up to 12V 17Ah (Battery Calculation Required)
PSU Output	7A

Inputs & Outputs

Zones	96
Loops	1
Auxiliary Output	1; 24V DC @ 300mA
Monitored Outputs	4
Sound Output @ 1m (Low) (db)	65+
Sound Output @ 1m (High) (db)	85+

Communication

Protocol Type	Custom (Closed)
----------------------	-----------------

Environment

Operating Temperature (°C)	+5 to +50
-----------------------------------	-----------

Standards BS EN 54-2, BS EN 54-4

Accessories

MAGDUOPK: Pack of 2 Keys
 BAT18: 12V 17Ah SLA Battery
 MAGPRO-PROG: Address Programming Tool For MAGPRO Devices
 MAGPRO96-L250: Single Loop Expander for 250 Devices
 MAGPRO-NIC: Network Interface Card
 MAGPRO Series Loop Devices and MAGPRO96GBB

