

Technical Specification



Product Code: PSPSF247S

Description:

Powersaver Plus Electronic 24/7 Fused Boost controller with Programmable Operations in Silver



General Information		Outputs	
Dimensions (mm)	86 x 86 x 35	Number of Outputs	1
Depth Without Back Box (mm)	12	Switched Output	230V AC, DPST
lush Mounting Back Box Depth (mm)	25	Maximum LED Lamp Load Rating (W)	200 @ 230V
Finish	Silver	Maximum Incandescent, Halogen	750
Display	LCD, Clear Indication Display	Lamp Load Rating (W)	
Materials	ABS	Maximum Fluorescent Lamp Load	500
Mounting	Surface and Flush Mounting	Rating (W)	
Warranty (Years)	3	Maximum Compact Fluorescent Lamp	100
Programming		Load Rating (W) Maximum Fluorescent Lamp Load	500
Programming Schedule 2	24 Hour, 5/2 Day & 7 Day	Rating (W)	500
Available Operations	Jp to 10 per Day		
Summer/Winter Time Change	les (Automatic)		
Memory Reserve	Permanent Reserve Setting		
Button Lock Yes			
	5 Minutes, 30 Minutes, 1 Hour, 2		
H	Hours, 4 Hours, or 6 Hours		
Supply & Power		_	
Supply Voltage (V AC)	230		
Frequency (Hz)	50		
Fuse Fitted (BS1362)			
Maximum Cable Size (mm ²)			
IEC Protection Class	Class II		
Environment			
Ingress Protection IF	20		
Operating Temperature (°C) 0	to +40		
Temperature Rating	40		
Supplied BS1362	13A Euse		

Accessories

PSPFUSE - Powersaver Plus Spare Fuses

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com



Page 1 of 1 (18/10/22) Errors & Omissions excluded. Specification is subject to change without notice.