

Technical Specification



Product Code: PSPSF24B

Description: Powersaver Plus Electronic 24 Hour Fused Boost controller with Programmable

Operations in Black



Genera	Infor	mation

General Information		
Dimensions (mm	n) 86 x 86 x 35	
Depth Without Back Box (mm	n) 12	
Flush Mounting Back Box Depth (mm	n) 25	
Finis	h Matt Black	
Displa	y LCD, Clear Indication Display	
Material	s ABS	
Mountin	g Surface and Flush Mounting	
Warranty (Years	s) 3	
Programming		
Programming Schedule	24 Hour	
Available Operations	Up to 10 per Day	
Summer/Winter Time Change	Yes (Automatic)	
Memory Reserve	Permanent Reserve Setting	
Button Lock	es	
Selectable Boost Durations	5 Minutes, 30 Minutes, 1 Hour, 2	
	lours, 4 Hours, or 6 Hours	
Supply & Power		
Supply Voltage (V AC	230	
Frequency (Ha	z) 50	
Fuse Fitted (BS1362	13A	
Maximum Cable Size (mm	2) 2.5 (Flex), 4.0 (Fixed)	

IEC Protection Class | Class |

Supplied BS1362 13A Fuse

Ingress Protection IP20
Operating Temperature (°C) 0 to +40
Temperature Rating T40

\sim	4		
u	ш	เต	IIS

Outputs	
Number of Outputs	1
Switched Output	240V AC, DPST
Maximum LED Lamp Load Rating (W)	200 @ 230V
Maximum Incandescent, Halogen Lamp Load Rating (W)	750
Maximum Fluorescent Lamp Load Rating (W)	500
Maximum Compact Fluorescent Lamp Load Rating (W)	100
Maximum Fluorescent Lamp Load Rating (W)	500

Accessories

Environment

PSPFUSE - Powersaver Plus Spare Fuses

