

## **Technical Specification**



Product Code: Q550.13.12

Astro Zone 2, 3 Pin Time Switch, 1 On/Off, Day Omit skips ON operation **Description:** 



| General Information                        |   | Outputs  |                    |
|--|---|--|--------------------|
| Dimensions (mm)                            | 146.5 x 105.7 x 82  | Number of Outputs  | 1                  |
| Display                                    | 24 Hour Dial  | Total Switch Rating  | 230V AC, 20A       |
| Timing Accuracy                            | 5 Minutes / Year  | Contact Type   | Switched Live SPST |
| Time Base                                  | Quartz Crystal  | Maximum LED Lamp Load Rating (W)                               | 3600 @ 230V        |
| Mounting                                   | Surface Mounting  | Maximum Inductive Current Rating                               | 5                  |
| Base Type                                  | 3 Pin   | (A) (0.6pf)  |                    |
| Warranty (Years)                           | 5   | Maximum Inductive Current Rating                               | 12                 |
| Programming                                |   | (A) (0.8pf)  |                    |
| Programming Schedule 24 Hour Program       |   | Maximum Incandescent, Halogen                                  | 3600               |
| Available Operations                       | 1 ON/OFF Period   | Lamp Load Rating (W)   | 1000               |
| Dial Calibration Zone 2                    |   | Maximum Fluorescent Lamp Load<br>Rating (W)                    | 1980               |
| Setting Accuracy +/- 3 Minutes             |   | Maximum Discharge (Sodium,<br>Mercury, Metal Halide) Lamp Load | 3600               |
| Sunrise/Sunset Time Offset (Mins) (+/-) 45 |   |  |                    |
|  | Yes (omits the "ON" operation)  | Rating (W)   |                    |
| Temporary Override Facility (Manual        |   | Maximum Fluorescent Lamp Load                                  | 1980               |
| ,  | "ON" and will Remain "OFF" Unit<br>Next "ON" Operation and Vice Versa | Rating (W)   |                    |
| Supply & Power                             |   |  |                    |
| Supply Voltage (V AC                       | 230   |  |                    |
| Power Consumption (W                       | 0.6   |  |                    |
| Power Consumption (mA                      | ) 0.6W @ 230V   |  |                    |
| Cable Size (mm²                            | 0.5 - 4   |  |                    |
| Power Reserve                              | 20 Days   |  |                    |
| IEC Protection Class                       | Class I (Must be Earthed)   |  |                    |
|  |   |  |                    |
| Environment                                |   |  |                    |

Accessories

110469: FD930 Conduit Box Time Switch

Operating Temperature (°C) 0 to +50













