

Technical Specification



Product Code: Q550.13.13

Description: Astro Zone 3, 3 Pin Time Switch, 1 On/Off, Day Omit skips ON operation



General Information		Outputs	
Dimensions (mm)	146.5 x 105.7 x 82	Number of Outputs	1
Display	24 Hour Dial	Total Switch Rating	230V AC, 20A
Timing Accuracy	5 Minutes / Year	Contact Type	Switched Live SPST
Time Base	Quartz Crystal	Maximum LED Lamp Load Rating (W)	3600 @ 230V
Mounting	Surface Mounting	Maximum Inductive Current Rating	5
Base Type	3 Pin	(A) (0.6pf)	
Warranty (Years)	5	Maximum Inductive Current Rating	12
Programming		(A) (0.8pf)	
Programming Schedule 24 Hour Program		Maximum Incandescent, Halogen	3600
Available Operations 1 ON/OFF Period		Lamp Load Rating (W) Maximum Fluorescent Lamp Load Rating (W)	1980
Dial Calibration Zone 3			
Setting Accuracy +/- 3 Minutes		Maximum Discharge (Sodium, Mercury, Metal Halide) Lamp Load Rating (W)	3600
Sunrise/Sunset Time Offset (Mins) (+/-) 45			
Day Omission Yes (omits the "ON" operation)			
,	ON" and will Remain "OFF" Unit	Maximum Fluorescent Lamp Load Rating (W)	1980
Next "ON" Operation and Vice Versa Supply & Power			
Supply Voltage (V AC)	230		
Power Consumption (W)	0.6		
Power Consumption (mA)	0.6W @ 230V		
Cable Size (mm ²)	0.5 - 4		
Power Reserve	20 Days		

Ingress ProtectionIP20Operating Temperature (°C)0 to +50

IEC Protection Class Class I (Must be Earthed)

Accessories

Environment

110469: FD930 Conduit Box Time Switch

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com



Page 1 of 1 (18/10/22) Errors & Omissions excluded. Specification is subject to change without notice.