

## **Technical Specification**



Product Code:Q551.14.12Description:Astro Zone 2, 3 Pin Time Switch, 2 On/Off



General Information		Outputs	
Dimensions (mm)	146.5 x 105.7 x 82	Number of Outputs	1
Display	/ 24 Hour Dial	Total Switch Rating	230V AC, 20A
Timing Accuracy	/ 5 Minutes / Year	Contact Type	Switched Live SPST
Time Base	Quartz Crystal	Maximum LED Lamp Load Rating (W)	3600 @ 230V
Mounting	Surface Mounting	Maximum Inductive Current Rating	5
Base Type	9 3 Pin	(A) (0.6pf)	
Warranty (Years	5	Maximum Inductive Current Rating	
Programming		(A) (0.8pf)	
Programming Schedule	24 Hour Program	Maximum Incandescent, Halogen Lamp Load Rating (W)	
Available Operations	2 ON/OFF Periods		
Dial Calibration	Zone 2	Maximum Fluorescent Lamp Load Rating (W)	1980
Setting Accuracy	+/- 3 Minutes	Maximum Discharge (Sodium,	3600
Sunrise/Sunset Time Offset (Mins)	(+/-) 45	Mercury, Metal Halide) Lamp Load	3000
Day Omission	No	Rating (W)	
Temporary Override Facility (Manual	Advance to "OFF", When Program	Maximum Fluorescent Lamp Load	1980
,	"ON" and will Remain "OFF" Unit Next "ON" Operation and Vice Versa	Rating (W)	
Supply & Power			
Supply Voltage (V AC	) 230		
Power Consumption (W	) 0.6		
Power Consumption (mA	) 0.6W @ 230V		
Cable Size (mm <sup>2</sup>	) 0.5 - 4		
Power Reserve	e 20 Days		

 Ingress Protection
 IP20

 Operating Temperature (°C)
 0 to +50

IEC Protection Class Class I (Must be Earthed)

Accessories

110469: FD930 Conduit Box Time Switch

Unit 7 Target Park, Shawbank Road, Lakeside, Redditch B98 8YN United Kingdom **T:** +44 (0)1527 515150 | **F:** +44 (0)1527 515143 **E:** info@espuk.com | **W:** espuk.com



Page 1 of 1 (18/10/22) Errors & Omissions excluded. Specification is subject to change without notice.