

Product Code: Q553.13.11

Description: Astro Zone 1, 4 Pin Time Switch, 1 On/Off & optional early off



General Information

| | |
|---|---|
| Dimensions (mm) | 146.5 x 105.7 x 82 |
| Display | 24 Hour Dial |
| Timing Accuracy | 5 Minutes / Year |
| Time Base | Quartz Crystal |
| Mounting | Surface Mounting |
| Base Type | 4 Pin |
| Warranty (Years) | 5 |
| Programming | |
| Programming Schedule | 24 Hour Program |
| Available Operations | 1 ON/OFF Period |
| Dial Calibration | Zone 1 |
| Setting Accuracy | +/- 3 Minutes |
| Sunrise/Sunset Time Offset (Mins) | (+/-) 45 |
| Day Omission | No |
| Temporary Override Facility (Manual Button) | Advance to "OFF", When Program "ON" and will Remain "OFF" Unit Next "ON" Operation and Vice Versa |

Outputs

| | |
|--|--------------|
| Number of Outputs | 1 |
| Total Switch Rating | 230V AC, 20A |
| Contact Type | SPST |
| Maximum LED Lamp Load Rating (W) | 3600 @ 230V |
| Maximum Inductive Current Rating (A)(0.6pf) | 5 |
| Maximum Inductive Current Rating (A)(0.8pf) | 12 |
| Maximum Incandescent, Halogen Lamp Load Rating (W) | 3600 |
| Maximum Fluorescent Lamp Load Rating (W) | 1980 |
| Maximum Discharge (Sodium, Mercury, Metal Halide) Lamp Load Rating (W) | 3600 |
| Maximum Fluorescent Lamp Load Rating (W) | 1980 |

Supply & Power

| | |
|-------------------------------|---------------------------|
| Supply Voltage (V AC) | 230 |
| Power Consumption (W) | 0.6 |
| Power Consumption (mA) | 0.6W @ 230V |
| Cable Size (mm ²) | 0.5 - 4 |
| Power Reserve | 20 Days |
| IEC Protection Class | Class I (Must be Earthed) |

Environment

| | |
|----------------------------|----------|
| Ingress Protection | IP20 |
| Operating Temperature (°C) | 0 to +50 |

Accessories

110469: FD930 Conduit Box Time Switch

