

Technical Specification

Product Code: Q553.13.12

Description: Astro Zone 2, 4 Pin Time Switch, 1 On/Off & optional early off





General Information		Outputs	
Dimensions (mm) 146.5 x 105.7 x 82	Number of Outputs	1
Display	/ 24 Hour Dial	Total Switch Rating	230V AC, 20A
Timing Accuracy	5 Minutes / Year	Contact Type	SPST
Time Base	Quartz Crystal	Maximum LED Lamp Load Rating (W)	3600 @ 230V
Mounting	Surface Mounting	Maximum Inductive Current Rating	5
Base Type	e 4 Pin	(A) (0.6pf)	
Warranty (Years) 5	Maximum Inductive Current Rating	12
Programming		(A) (0.8pf)	
Programming Schedule	24 Hour Program	Maximum Incandescent, Halogen	3600
Available Operations	1 ON/OFF Period	Lamp Load Rating (W)	1000
Dial Calibration	Zone 2	Maximum Fluorescent Lamp Load Rating (W)	1980
Setting Accuracy	+/- 3 Minutes	Maximum Discharge (Sodium, Mercury, Metal Halide) Lamp Load Rating (W)	3600
Sunrise/Sunset Time Offset (Mins)	(+/-) 45		
Day Omission	No		
Temporary Override Facility (Manual	Advance to "OFF", When Program "ON" and will Remain "OFF" Unit	Maximum Fluorescent Lamp Load	1980
,	Next "ON" Operation and Vice Versa	Rating (W)	
Supply & Power			
Supply Voltage (V AC	230		
Power Consumption (W	0.6		
Power Consumption (mA) 0.6W @ 230V		
Cable Size (mm²	?) 0.5 - 4		
Power Reserv	e 20 Days		
IEC Protection Clas	s Class I (Must be Earthed)		
Environment			

Accessories

110469: FD930 Conduit Box Time Switch

Ingress Protection IP20
Operating Temperature (°C) 0 to +50











