

## **Technical Specification**

ESP. ScolmoreGROUP

Product Code: Q553.14.12

**Description:** Astro Zone 2, 4 Pin Time Switch, 2 On/Offs



General Information		Outputs	
Dimensions (mm	) 146.5 x 105.7 x 82	Number of Outputs	1
Displa	y 24 Hour Dial	Total Switch Rating	230V AC, 20A
Timing Accurac	y 5 Minutes / Year	Contact Type	SPST
Time Bas	e Quartz Crystal	Maximum LED Lamp Load Rating (W)	3600 @ 230V
Mounting	g Surface Mounting	Maximum Inductive Current Rating	5
Base Type	e 4 Pin	(A) (0.6pf)	
Warranty (Years	5) 5	Maximum Inductive Current Rating	12
Programming		(A) (0.8pf)	
Programming Schedule	24 Hour Program	Maximum Incandescent, Halogen Lamp Load Rating (W) Maximum Fluorescent Lamp Load Rating (W)	
Available Operations	0		
Dial Calibration	Zone 2		
Setting Accuracy	+/- 3 Minutes	Maximum Discharge (Sodium, Mercury, Metal Halide) Lamp Load Rating (W)	3600
Sunrise/Sunset Time Offset (Mins)	(+/-) 45		
Day Omission	No		
Temporary Override Facility (Manual Button)	Advance to "OFF", When Program "ON" and will Remain "OFF" Unit Next "ON" Operation and Vice Versa	Maximum Fluorescent Lamp Load Rating (W)	1980
Supply & Power			
Supply Voltage (V AC	230		
Power Consumption (W	0.6		
Power Consumption (mA	(a) 0.6W @ 230V		
Cable Size (mm	2) 0.5 - 4		
Power Reserv	e 20 Days		
IEC Protection Clas	S Class I (Must be Earthed)		
Environment			
Ingress Protection	IP20		
Operating Temperature (°C)	0 to +50		

Accessories

110469: FD930 Conduit Box Time Switch











