



Description: 8 Channel Full HD 1TB DVR





General Information		Recording		
Dimensions (mm) 30	00 x 227 x 53	Internal HDD	1TB (1 x SATA)	
Materials St	eel - Body	eSATA Connection	1 SATA	
AE	BS - Faceplate	Video/Audio Compression	H.265	
Supply & Power		Recording Resolution	1080P @15fps	
Operating Voltage (V DC)	12	Record Rate (Main Stream)	8 Channels @1080P	
Power Consumption (mA)		Recording Mode	Manual/Motion Detection/Schedule	
Inputs & Outputs		Environment		
Video Input Channels (BNC) 8		Operating Temperature	e (°C) 0 to +55	
Audio Input Channels (RCA) 4		Relative Humidity Resistanc	e (%) 10 – 90	
Audio Output Channels (RCA) 1				
System				
Operating System LINUX				
Media Information				
Display Video Outp	1 x HDMI, 1 x VGA & 1 x BNC			
Display Sp	1, 4, 9 & 12			
Display Resolution	ns 1024x768, 1280×720, 1280×10	1024x768, 1280×720, 1280×1024, 1440×900, 1920×1080, 1080x1440, 3840x2160		
Sync Playbac	8Ch 1080P playback			
Backup Mod	USB2.0 devices			
Network				
Interfac	1 SATA			
Network Connection	Ethernet (RJ45 10M/100M)			
Network Function	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP			
Network Monitorin	CMS Windows & Mac, Android & iPhone apps			
NOTWORK WIGHTEDITI	2 (1 Front & 1 Back)			

Compatible Products Compatible with the range of RHD series of analogue HD bullet and dome cameras

Accessories **Features**

CAB-10: 10M Power and BNC Video Cable CAB-20: 20M Power and BNC Video Cable

CAB-40: 40M Power and BNC Video Cable CAB-80: 80M Power and BNC Video Cable

CAB-BNC: BNC Cable Connector

HDBALUNV: Single Channel HD Passive Balun

HDBALUNVP: Single Channel HD Video and Power Balun

HDBALUNVPCT: Single Channel HD Video and Power Transmitter Balun

Included)

Line Cross Detection Perimeter Intrusion Detection











