

Technical Specification

Product Code: SHDV116R16TB

Description: HDview Analogue 4MP 16CH DVR 16TB





General Information		Recording		
Dimensions (mm) 380 x 340 x 50			Maximum Capacity	
Warranty (Years) 3				8 Terabytes per SATA connection
Supply & Power		Storage Type	Internal HDD:16TB	
Operating Voltage (V DC) 12		SATA Connection(s)		
Power Consumption (mA) <20W (Without Hard Disk)		Recording Resolution		
Inputs & Outputs				1080p @ 25 FPS (PAL)
Alarm Inputs 16		-		Manual, Schedule, Alarm
Alarm Outputs			Environment	
Video Input Channels (BNC)	•		Operating Temperature (°C) -10 to +50	
. ,		nboard), 12 (Via DE-15 Socket)		
Audio Output Channels (RCA)		()		
Media Information				
Display Video C	utput	1 x HDMI, 1 x VGA, 1 x BNC		
		1, 4, 6, 8, 9, 10, 12, 13, 14, 16, 1	7, 19, 20, 22 & 25	
Display Resolutions		HDMI: 1024x768, 1280x720, 1280x1024, 1440x900, 1920x1080, 2560x1440, 3840x2160/EDID VGA: 1024x768, 1280x720, 1280x1024, 1440x900, 1920x1080 BNC: 704x576		
Sync Playback		Maximum 16 Channels		
Backup Mode		Network and USB2.0 (Up to 32GB Storage Medium Supported)		
Hardware Reset		Yes		
Network				
Interface		2 x USB, 1 x RS485		
Network Connection		RJ45; 10/100 BASE-T		
Network Monitoring		Mobile app, Windows & Mac Client, Web Interface		
Supplied 1 x Sys	tem Po			SB Mouse (0.5m), 1 x C13 IEC Cable
FHDVC MON18 MON23 MON23	Range 18PTz L: 18 L: 21. L: 23.	ge of Cameras e of Cameras f: 4.7-84.6mm 2MP Varifocal HD F .5" LED CCTV Monitor 5" LED CCTV Monitor 8" LED CCTV Monitor 1.5" LED 4K CCTV Monitor	Pan, Tilt and Zoom (PTZ) Camera	
Additional Information Playba		ction: Fast Forward & Reverse (2x (1/2x, 1/4x, 1/8x, 1/16x)	ς, 4x, 8x, 16x)	

Accessories Features

DVRPSU4: 12V DC 5 Amp Power Supply Unit HDVIP1632RRMB: Rack Mount Bracket

CPS18W: 18 Way 12V DC 10 Amp CCTV Power Supply

Line Cross Detection
Perimeter Intrusion Detection
Premium Surveillance Hard Disk Drive Pre-installed
Up-the-Coax (UTC) Protocol Supported







