

## Multi Way Video Door Entry

**Product Code:** SP1APDSMW

**Description:** MultiWay Video Door Station with Custom Apartment Addresses



### General Information

Dimensions (mm)	200 x 87 x 53
Materials	Aluminium Alloy
Mounting	Surface & Flush (requires APDSKPFMS) Mounted
Weight (Kg)	0.64
Warranty (Years)	3

### Media Information

Illumination	5 White light LEDs
Sensitivity (Lux)	0.1
Sensor Size (")	1/3
Lens size (mm)	3.6
Viewing Angle (°)	70
Audio	Full Duplex

### Programming

User Interaction	0 - 9, * and #
Code lengths	2 - 6
Maximum Call-able address	Subject to Requirement
Maximum Access Codes	32 PINs, 99 (When set to Multi-Way)

### Environment

Ingress Protection	IP55
Operating Temperature (°C)	-20 to +40

**Supplied** Fixing Screws, and Wall Plugs, User Manual

**Accessories** EVBPSBB: 12V Lock power supply with battery backup  
 APPOWMW: Aperta Multiway power supply  
 APSEPMW: Aperta Multiway BUS Separator  
 APMONW, APMONB, APMONWG, APMONBG, APAUDH, APAUDHBLK: Compatible Aperta Monitors  
 ENTERD: Flush Electric Lock  
 ENTERD-YLR: Surface Electric Lock

### Supply & Power

Operating Voltage (V AC)	
Operating Voltage (V DC)	24 (BUS)
Global Selections	Normally Open or Normally Closed; Volt-Free or 12V DC300mA
Effective Distance to PowerSupply (M)	50
Lock outputs	2

### Network

Recommended BUS Cable	Cat5e or higher
Communication Protocol	BUS

### Features

Outdoor Station rings so that the user knows whether the call has been answered, calls last up to 30 seconds

### Accessories

EVBPSBB: 12V Lock power supply with battery backup  
 APPOWMW: Aperta Multiway power supply  
 APSEPMW: Aperta Multiway BUS Separator  
 APMONW, APMONB, APMONWG, APMONBG, APAUDH, APAUDHBLK: Compatible Aperta Monitors  
 ENTERD: Flush Electric Lock  
 ENTERD-YLR: Surface Electric Lock

**Additional Information** Simple 2-core Installation  
 High-Resolution Colour Camera  
 Can be Customed to Customers Requirements  
 Can Call Address Range up to 32 Consecutive

