

Technical Specification

Quantity



Product Code: UDTAKITG

Description: Indication, Pull Cord and Reset Modules for Assistance Alarm Kit







Component 1 Description

UDTAPCMG - Pull Cord Module

Component 2 Description

UDTAPLBMG - Power, Light and Buzzer Module

Quantity

General Information

| Dimensions (mm | 87 x 87 x 41 | | | |
|------------------------------|---|--|--|--|
| Colou | Grey | | | |
| Light Reflectance Value (LRV | 32 | | | |
| Pull Cord Length (m | 3 (Including 2 Triangular Bangles) | | | |
| Plate Size | Single Gang | | | |
| Materials | Anti-Microbial ABS | | | |
| Mounting | Surface or Flush (Surface Box Included) | | | |
| Anti-Ligature | Yes | | | |
| Supply & Power | | | | |
| Operating Voltage (V DC) | 12 | | | |
| Maximum Cable Size (mm²) | 1.5 | | | |
| Power Consumption (W) | 0.3 | | | |
| Environment | | | | |
| Ingress Protection IP20 | | | | |
| | | | | |

| Genera | Lle | for | ma | tio | 1 |
|--------|-----|-----|----|-----|---|

| General Information | |
|-----------------------------------|--|
| Dimensions (mm) | 87 x 87 x 41 |
| Plate Size | Single Gang |
| Colour | Grey |
| Light Reflectance Value (LRV) | 32 |
| Materials | Anti-Microbial ABS |
| Mounting | Surface or Flush (Surface Box Included) |
| Indication | LED illuminates in red when in alarm state |
| Activated Buzzer Sound Level (db) | >80 |
| Purpose | Activation and Reset Circuits |
| Maximum Cable Size (mm²) | 1.5 |
| Power Consumption (A) | 0.2 |
| Battery Backup | A23 Battery |
| Input Type | Ground & 2 live circuits - X1 & X2 |
| Activation Type | Energise with a Normally Open Clean Contact |
| Output Type | 1 Switched Live sharing common ground Separate output for additional sounders |
| Number of Outputs | 2 |
| Output Rating | 12V 500mA |
| Ingress Protection | IP20 |

Component 3 Description

Storage Temperature (°C)

Quantity

UDTAREMG - Assistance Alarm Reset Module

General Information

Dimensions (mm) 87 x 87 x 41

Plate Size Single Gang
Colour Grey

Light Reflectance Value (LRV) 32

Materials Anti-Microbial ABS

Mounting Surface or Flush (Surface Box Included)

Indication LED illuminates in red when in alarm state

Buzzer Sound Level When Activated (db) >80

Operating Voltage (V DC) 12

Maximum Cable Size (mm²) 1.5

Power Consumption (W) 0.9

Ingress Protection IP20















Technical Specification



Product Code: UDTAKITG

Indication, Pull Cord and Reset Modules for Assistance Alarm Kit Description:

Warranty Years 2

Additional Information Part M1 of the Building Regulations refers to the 'Access and Use' of a building and its facilities with Sections 4.25 to 4.29 then refining the use and design considerations of switches, outlets and controls. Beacon grey assistance alarm products work perfectly with these regulations. Part of the requirements of Part M1 is to aid disabled people within their surroundings, being able to activate a light, socket or control within arms length, for the visually impaired being able to identify the units' position against its surrounding décor, and for the infirm a suitable pull-cord switch to raise the alarm in the event of an emergency

Features Accessories

Anti-Ligature Red Pull Cord

UDTAPLBMG: Assistance Alarm, Power, Light and Buzzer Module UDTALBMG: Assistance Alarm Light and Buzzer Module UDTAPCMG: Assistance Alarm Pull Cord Module UDTASPC: Assistance Alarm Replacement Pull Cord UDTAREMG: Assistance Alarm Reset Module

