



General Information

Dimensions (mm)	87 x 87 x 41
Pull Cord Length (m)	3 (Including 2 Triangular Bangles)
Plate Size	Single Gang
Colour	Grey
Light Reflectance Value (LRV)	32
Materials	Anti-Microbial ABS
Mounting	Surface or Flush (Surface Box Included)
Anti-Ligature	Yes
Indication	LED illuminates in red when in alarm state
Warranty (Years)	2

Supply & Power

Operating Voltage (V DC)	12
Maximum Cable Size (mm ²)	1.5
Power Consumption (W)	0.3

Environment

Ingress Protection	IP20
--------------------	------

Supplied 1 x Backbox, Installation Bolts, User Manual

Additional Information Part M1 of the Building Regulations refers to the 'Access and Use' of a building and its facilities with Sections 4.25 to 4.29 then refining the use and design considerations of switches, outlets and controls. Beacon grey assistance alarm products work perfectly with these regulations. Part of the requirements of Part M1 is to aid disabled people within their surroundings, being able to activate a light, socket or control within arms length, for the visually impaired being able to identify the units' position against its surrounding décor, and for the infirm a suitable pull-cord switch to raise the alarm in the event of an emergency

Features

Anti-Microbial Properties, Anti-Ligature Red Pull Cord

Accessories

- UDTAPLBMG: Assistance Alarm, Power, Light and Buzzer Module
- UDTALBMG: Assistance Alarm Light and Buzzer Module
- UDTAPCMG: Assistance Alarm Pull Cord Module
- UDTASPC: Assistance Alarm Replacement Pull Cord
- UDTAREMG: Assistance Alarm Reset Module