



General Information

Dimensions (mm)	87 x 87 x 41
Plate Size	Single Gang
Colour	Grey
Light Reflectance Value (LRV)	32
Materials	Anti-Microbial ABS
Mounting	Surface or Flush (Surface Box Included)
Indication	LED illuminates in red when in alarm state
Buzzer Sound Level When Activated (db)	>80
Purpose	Activation and Reset Circuits
Warranty (Years)	2

Supply & Power

Operating Voltage (V AC)	100 - 230
Maximum Cable Size (mm ²)	1.5
Power Consumption (A)	0.2
Battery Backup	Yes

Inputs

Input Type	Ground & 2 live circuits - X1 & X2
Activation Type	Energise with a Normally Open Clean Contact

Outputs

Number of Outputs	2
Output Type	1 Switched Live sharing common ground Separate output for additional sounders
Output Rating	12V 500mA

Environment

Ingress Protection	IP20
--------------------	------

Supplied 1 x Backbox, Installation Bolts, User Manual

Additional Information Part M1 of the Building Regulations refers to the 'Access and Use' of a building and its facilities with Sections 4.25 to 4.29 then refining the use and design considerations of switches, outlets and controls. Beacon grey assistance alarm products work perfectly with these regulations. Part of the requirements of Part M1 is to aid disabled people within their surroundings, being able to activate a light, socket or control within arms length, for the visually impaired being able to identify the units' position against its surrounding décor, and for the infirm a suitable pull-cord switch to raise the alarm in the event of an emergency

Features

Built in Battery Backup with Supplied A23 Battery, Sounder Buzzes Intermittantly When Battery Needs Replacing, Anti-Microbial Properties.

Accessories

UDTAPLBMG: Assistance Alarm, Power, Light and Buzzer Module
 UDTALBMG: Assistance Alarm Light and Buzzer Module
 UDTAPCMG: Assistance Alarm Pull Cord Module
 UDTAREMG: Assistance Alarm Reset Module